



Model:		*2*2.0MP WIFI Dual-lens PTZ camera (excluding TF Card) * Specification X1 * Screw pack X1 * Stents X1 * Power adapter X1 * Power cord X1	
			
Packing box size(mm)/weight(kg)		152*88*88mm/0.35kg	
Outer box size(mm)/weight(kg)		460*320*460mm/17.5KG/50pcs	
Specification parameter			
system	Main Processor	Dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog	
	image sensor	2 m 1/2.8" SC233A High performance CMOS sensors	
	Operation System	Embedded LINUX operating system	
	Video Compression	Smart H.265X	
	APP	ICSEE (Android and IOS support)	
Video	High Definition	2*2MP	
	Image resolution	Main code stream: 1920*2160@12fps; Substream: 640*720@12fps	
	Minimum illumination	0.01 LUX/pro series	
	Lens	3.6mm(standard)	
	Perspective	92 °	
	Turn video	Flip up and down/flip side to side	
lighting	Light control mode	Starlight full color/intelligent warning/infrared night vision	
	Number of lights	8 red lights +4 white lights	
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°	
	Turn PTZ	Flip up and down/flip side to side	
Audio	Coding standard	G.711	
	Mitou	support	
	Two-way Speech	support	
Record management	Video file size	≈6G/ day	
	Record Mode	Manual video recording, dynamic detection video recording, timing	
	Video storage	TF card/cloud	
	storage	Cloud Storage +TF Local Video recording (128GB Max)	
	Remote playback	support	
	Image capture	support	
Network	WIFI	2.4G WIFI 802.11b/g/n	
	Pairing	Bluetooth distribution network addition, AP hotspot addition, QR code scan	
	Network Protocol	TCP/IP, ONVIF, RTSP	
extension	Reset key	support	
	Human tracking	support	
	360degree coordinate	support	
power supply	Power	DC 5V 1.6A	
	power interface	Micro Type-A	
work environment	Suitable place	outdoor、Home、shop、School、factory;	
	Installation mode	Wall hanging, lifting, flat	
	Working	-20℃ — +55℃	
	Working humidity	10%—90%	